


ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.



Power roller conveyor featured with optional power assist unit.

NESTAFLEX
FLEXIBLE CONVEYORS

Intra Storage Systems
5555 McFadden Ave
Huntington Beach, CA
714-895-5128

1.6



ALL POWER ROLLER CONVEYOR

The NESTAFLEX 1.6 POWER ELITE all roller power conveyor has a capacity of 100 pounds per lineal foot (level surface). It operates on DC drive motors with a 120VAC converter, delivering variable speeds of 0-120 feet per minute PLUS standard reversible action.

The POWER ELITE with its innovative design, requires less storage space when fully retracted, and with its ALL-BOLTED construction and durable design, this conveyor is the smart solution for distribution centers where there is high volume cross docking, loading and unloading applications. With features such as built in impact conveyor, electronic indexing, zero pressure accumulation, and power assist, the POWER ELITE is the next step in automating your application.

The 1.6 is also a smart solution in packaging and manufacturing applications allowing greater product control and maximizing worker efficiency. Like all NESTAFLEX conveyors, the 1.6 POWER ELITE is portable, expandable and can be configured to meet specific material handling needs. **The all roller power conveyor is also available as the 1.9 POWER PLUS HD using 1.9 diameter steel rollers.**

CONVEYOR OPTIONS



Impact Conveyor



Power Truck Loader
with Guide Track and
Herringbone transition



Zero Pressure
Accumulation



Power Assist Unit

INSTALLATION

We also offer custom installation from our factory trained technicians!

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

Model Length	1.6 Power Elite 18" Widths	1.6 Power Elite 24" Widths	1.6 Power Elite 30" Widths	1.6 Roller Contracted Length	1.9 Roller Contracted Length	3" Axle Centers Extended Length	4" Axle Centers Extended Length	5 1/4" Axle Centers Extended Length
12	pRL18012S1201.6	pRL24012S1201.6	pRL30012S1201.6	4' 2"	5' 2"	6' 11"	9' 2"	12' 0"
16	pRL18016S1201.6	pRL24016S1201.6	pRL30016S1201.6	5' 4"	6' 7"	8' 11"	11' 10"	15' 5"
19	pRL18019S1201.6	pRL24019S1201.6	pRL30019S1201.6	6' 9"	8' 4"	11' 2"	14' 9"	19' 3"
23	pRL18023S1201.6	pRL24023S1201.6	pRL30023S1201.6	7' 11"	9' 10"	13' 2"	17' 5"	22' 9"
26	pRL18026S1201.6	pRL24026S1201.6	pRL30026S1201.6	9' 2"	11' 3"	15' 2"	20' 1"	26' 3"
30	pRL18030S1201.6	pRL24030S1201.6	pRL30030S1201.6	10' 4"	12' 8"	17' 2"	22' 9"	29' 9"
33	pRL18033S1201.6	pRL24033S1201.6	pRL30033S1201.6	11' 9"	14' 5"	19' 5"	25' 8"	33' 6"
37	pRL18037S1201.6	pRL24037S1201.6	pRL30037S1201.6	12' 11"	15' 10"	21' 5"	28' 4"	37' 0"
40	pRL18040S1201.6	pRL24040S1201.6	pRL30040S1201.6	14' 1"	17' 4"	23' 5"	31' 0"	40' 6"
51	pRL18051S1201.6	pRL24051S1201.6	pRL30051S1201.6	15' 4"	18' 9"	25' 5"	33' 8"	44' 0"
54	pRL18054S1201.6	pRL24054S1201.6	pRL30054S1201.6	16' 9"	20' 6"	27' 8"	36' 7"	47' 9"
58	pRL18058S1201.6	pRL24058S1201.6	pRL30058S1201.6	17' 11"	21' 11"	29' 8"	39' 3"	51' 3"
61	pRL18061S1201.6	pRL24061S1201.6	pRL30061S1201.6	19' 1"	23' 5"	31' 8"	41' 11"	54' 9"
65	pRL18065S1201.6	pRL24065S1201.6	pRL30065S1201.6	20' 4"	24' 10"	33' 8"	44' 7"	58' 3"
68	pRL18068S1201.6	pRL24068S1201.6	pRL30068S1201.6	21' 9"	26' 7"	35' 11"	47' 6"	62' 0"
72	pRL18072S1201.6	pRL24072S1201.6	pRL30072S1201.6	22' 11"	28' 0"	37' 11"	50' 2"	65' 6"
75	pRL18075S1201.6	pRL24075S1201.6	pRL30075S1201.6	24' 4"	29' 9"	40' 2"	53' 1"	69' 3"
				25' 6"	31' 2"	42' 2"	55' 9"	72' 9"
				26' 11"	32' 11"	44' 5"	58' 8"	76' 6"

NESTAFLEX 1.6 STANDARD FEATURES AND OPTIONS

NESTAFLEX
FLEXIBLE CONVEYORS

1.6

ALL POWER ROLLER CONVEYOR
Other Options Available

We encourage you to take advantage of our free application analysis to determine the operational efficiencies that can be gained from the Nestaflex 1.6 and the flexible material handling—smart solutions team.

CONSTRUCTION

All-steel BOLTED construction.

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. Lengths can be tailored to your specific application.

CAPACITY

100 pounds per linear foot—level capacity. On 3 degree incline—50 pounds per linear foot.

LEGS

Legs are made from heavy-duty steel tubing and have welded, double horizontal cross braces.

SIDE LINKS

1.72" wide side links are made from steel and feature all bolted construction.

HEAVY DUTY CASTERS

Standard 6" x 2" swivel casters. Optional 8" x 2" casters available. Both have steel foot brake that locks wheel and swivel simultaneously.

AXLES

Standard axle centers are 5 1/4". Optional 4" and 3" axle centers are available to convey small cartons.

PACKAGE STOP

Electronic/mechanical package stop is optional.

HEAVY-DUTY ROLLERS

1.6" diameter rollers (1.9" on the 1.9 model) are made from 16-gauge steel and have precision bearings and a 1/4" diameter polyurethane drive belt.

WARRANTY

One-year factory warranty.

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.



NESTAFLEX
FLEXIBLE CONVEYORS

226

GRAVITY SKATE WHEEL CONVEYOR



Designed to expand, contract and move easily, the **226** is a self tracking, gravity skate wheel conveyor that has a per lineal foot capacity of 226 pounds! This unit is engineered to handle multi-sized cartons in low to medium volume applications.

The **ALL-STEEL** construction provides unmatched structural integrity, whether the conveyor is extended, compacted or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow. The **NESTAFLEX 226** is the choice for use in retail store level applications, packaging areas, assembly lines and


in low volume shipping and receiving departments. Call us today to learn more at 800.669.1501 or visit our website at www.flexmh.com



CONVEYOR OPTIONS



Dockless Receiving



Swing Stick



T-Junction



Flexible Side Rails

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

14" WIDTHS		18" WIDTHS		24" WIDTHS		LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS		
Model 226	*Skate Wheels Per Axle	Model 226	Skate Wheels Per Axle	Model 226	**Skate Wheels Per Axle	Contracted/ Extended	Leg Sets Per Unit	Bed Sections Per Unit
22614008	6	22618008	6	22624008	8	2' 4" - 8' 11"	3	2
22614012	6	22618012	6	22624012	8	3' 3" - 12' 10"	4	3
22614016	6	22618016	6	22624016	8	4' 3" - 16' 9"	5	4
22614020	6	22618020	6	22624020	8	5' 2" - 20' 9"	6	5
22614024	6	22618024	6	22624024	8	6' 2" - 24' 8"	7	6
22614028	6	22618028	6	22624028	8	7' 1" - 28' 7"	8	7
22614032	6	22618032	6	22624032	8	8' 1" - 32' 6"	9	8
22614036	6	22618036	6	22624036	8	9' 0" - 36' 5"	10	9
22614040	6	22618040	6	22624040	8	10' 0" - 40' 5"	11	10
22614044	6	22618044	6	22624044	8	10' 11" - 44' 4"	12	11
22614048	6	22618048	6	22624048	8	11' 11" - 48' 3"	13	12
22614052	6	22618052	6	22624052	8	12' 10" - 52' 3"	14	13
22614056	6	22618056	6	22624056	8	13' 10" - 56' 2"	15	14
22614060	6	22618060	6	22624060	8	14' 9" - 60' 1"	16	15

*8 Skate-wheel option available on 14" wide models **10 skate wheel option available on 24" wide models

NESTAFLEX 226 STANDARD FEATURES AND OPTIONS

NESTAFLEX
FLEXIBLE CONVEYORS

226

SKATE WHEEL
OPTIONS

N-Red Nylon



P-Black Polymer



S-Steel

CONSTRUCTION

All steel construction.

CONVEYOR FORMATS

Available in 14", 18" and 24" widths. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

N-Red Nylon with nylon bushing for high-impact, short conveyors runs.

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

Stand adjustable heights from 28" to 44". Other height adjustments available.

LEGS

Zinc plated, heavy duty leg supports 1 1/4" square steel tubing and feature a welded cross member for added strength.

HEAVY DUTY CASTERS

Standard 5" x 1 1/2" swivel casters with steel brakes.

SIDE LINKS

Conveyor side links are made of 11 gauge steel.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

BOX STOP/HANDLE

Retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

18 month factory warranty.

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



NESTAFLEX
FLEXIBLE CONVEYORS

275

GRAVITY SKATE WHEEL CONVEYOR



**4-Point Leg
Connection**

The 275 features ALL BOLTED CONSTRUCTION and is a heavy duty, gravity conveyor that features DOUBLE welded cross braces and reinforced inner legs for added support. The ALL-STEEL reinforced leg and frame design provides the strength necessary to handle heavy cartons and industrial atmospheres.

The ALL-STEEL construction provides unmatched structural integrity, whether the conveyor is extended, compacted or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow. The NESTAFLEX 275 has a proven track record in the manufacturing field and is the choice for

medium to high volume shipping and receiving departments. Call us today to learn more at 800.669.1501 or visit our website at www.flexmh.com



**Adjustable
Height Legs**

CONVEYOR OPTIONS



6 x 2 Caster with Brake



Flexible Side Rails



Impact Conveyor



Swing Gate

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

18" WIDTHS		24" WIDTHS		30" WIDTHS		LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS		
Model 275	Skate Wheels Per Axle	Model 275	Skate Wheels Per Axle	Model 275	Skate Wheels Per Axle	Contracted/ Extended	Leg Sets Per Unit	Bed Sections Per Unit
27518008	6	27524008	9	27530008	12	2' 7" - 8' 6"	3	2
27518012	6	27524012	9	27530012	12	3' 7" - 12' 2"	4	3
27518016	6	27524016	9	27530016	12	4' 8" - 15' 10"	5	4
27518020	6	27524020	9	27530020	12	5' 8" - 19' 6"	6	5
27518024	6	27524024	9	27530024	12	6' 8" - 23' 2"	7	6
27518028	6	27524028	9	27530028	12	8' 2" - 28' 0"	8	7
27518032	6	27524032	9	27530032	12	9' 2" - 31' 8"	9	8
27518036	6	27524036	9	27530036	12	10' 3" - 35' 4"	10	9
27518040	6	27524040	9	27530040	12	12' 1" - 41' 10"	12	11
27518044	6	27524044	9	27530044	12	13' 1" - 45' 6"	13	12
27518048	6	27524048	9	27530048	12	14' 4" - 49' 5"	14	13
27518052	6	27524052	9	27530052	12	15' 4" - 53' 1"	15	14
27518056	6	27524056	9	27530056	12	16' 5" - 56' 9"	16	15
27518060	6	27524060	9	27530060	12	17' 5" - 60' 5"	17	16

Also available in 36" widths.

NESTAFLEX 275 STANDARD FEATURES AND OPTIONS

NESTAFLEX
FLEXIBLE CONVEYORS

275

SKATE WHEEL
OPTIONS

N-Red Nylon



P-Black Polymer



S-Steel

CONSTRUCTION

All-steel BOLTED construction.

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. 36" available upon request. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

N-Red Nylon with nylon bushing for high-impact, short conveyors runs.

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

Standard adjustable heights from 28" to 36". Other height options available.

LEGS

Zinc plated 1 1/8 O.D. 12 gauge steel tubing with adjustable re-inforced inner leg and double cross braces. Incremental height marks are provided on outer leg to facilitate uniform height adjustment. Four point bolted leg connection to skate wheel axles and side links.

HEAVY DUTY CASTERS

Standard 5" x 1 1/2" casters with heavy duty stem. Casters with swivel/wheel lock pedal brakes are provided on the first and last legs. 6" x 2" casters available for added strength and mobility.

SIDE LINKS

Conveyor side links are made of 7 gauge steel and feature bolted construction.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

BOX STOP/HANDLE

Standard retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

Two year factory warranty.

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501

ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.



SMART DESIGNS COME FROM SMART SOLUTIONS.



Nestaflex 375 truck loading system featured with herringbone transition and guide track system.



4-Point Leg Connection

NESTAFLEX 375

The ALL-BOLTED Nestaflex 375 is designed for use in **high-volume** shipping and receiving applications, especially distribution centers. This exceptional conveyor is application specific to meet individual material handling requirements. The 375 is a heavy duty, self tracking gravity skate wheel conveyor that has a per lineal foot capacity of 375 pounds! The ALL-BOLTED steel frame construction and rugged 4 point leg connection provide the structural integrity and durability needed for today's most demanding applications!

NESTAFLEX®
FLEXIBLE CONVEYORS

375



GRAVITY SKATE WHEEL CONVEYOR

NESTAFLEX 375 TRUCK LOADING SYSTEM

The Nestaflex 375 is the leading expandable conveyor for outbound product and can be equipped with several engineered options to maximize performance. Fixed height perpendicular legs make sure your conveyor pitch remains constant and provides gravity flow, while the **Herringbone Transition** centers your product as it goes from your fixed conveyor to the truck loading system. Storage is made simple by the **Guide Track System** designed to allow you to store the 375 under your fixed conveyor to maximize control and storage space.

NESTAFLEX 375 RECEIVING SYSTEM

The Nestaflex 375 is also the conveyor of choice for your high volume receiving applications. Larger casters help move the conveyor easily over dock plates. The optional receiving impact conveyor can be built into your system to help add longevity to the overall system and reduces maintenance issues. We encourage you to take advantage of our free application analysis to determine the operational efficiencies that can be gained from the **Nestaflex 375 and the flexible material handling-smart solutions team.**

CONVEYOR OPTIONS



Herringbone Transition



Impact Conveyor



Powered Assist



8 x 2 caster

INSTALLATION

We also offer custom installation from our factory trained technicians!

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501



SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

18" WIDTHS		24" WIDTHS		30" WIDTHS		LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS		
Model 375	Skate Wheels Per Axle	Model 375	Skate Wheels Per Axle	Model 375	Skate Wheels Per Axle	Contracted/ Extended	Leg Sets Per Unit	Bed Sections Per Unit
37518008	6	37524008	9	37530008	12	2' 7" - 8' 6"	3	2
37518012	6	37524012	9	37530012	12	3' 7" - 12' 2"	4	3
37518016	6	37524016	9	37530016	12	4' 8" - 15' 10"	5	4
37518020	6	37524020	9	37530020	12	5' 8" - 19' 6"	6	5
37518024	6	37524024	9	37530024	12	6' 8" - 23' 2"	7	6
37518028	6	37524028	9	37530028	12	8' 2" - 28' 0"	8	7
37518032	6	37524032	9	37530032	12	9' 2" - 31' 8"	9	8
37518036	6	37524036	9	37530036	12	10' 3" - 35' 4"	10	9
37518040	6	37524040	9	37530040	12	12' 1" - 41' 10"	12	11
37518044	6	37524044	9	37530044	12	13' 1" - 45' 6"	13	12
37518048	6	37524048	9	37530048	12	14' 4" - 49' 5"	14	13
37518052	6	37524052	9	37530052	12	15' 4" - 53' 1"	15	14
37518056	6	37524056	9	37530056	12	16' 5" - 56' 9"	16	15
37518060	6	37524060	9	37530060	12	17' 5" - 60' 5"	17	16

Also available in 36" widths.

NESTAFLEX 375 STANDARD FEATURES AND OPTIONS

NESTAFLEX
FLEXIBLE CONVEYORS

375

SKATE WHEEL
OPTIONS

P-Black Polymer



S-Steel

CONSTRUCTION

All-steel BOLTED construction.

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. 36" available upon request. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

Preset individual leg heights are application specific. To maintain gravity flow, a pitch of 5/16 per foot is recommended. Conveyor height is engineered to your specific application.

LEGS

Zinc plated 1 1/8 O.D. 12 gauge steel tubing with reinforced inner leg and double cross braces. Four point bolted leg connection to skate wheel axles and side links.

HEAVY DUTY CASTERS

Standard 6"x 2" casters with heavy duty stem. Casters with swivel/wheel lock pedal brakes are provided on the first and last legs. 8" x 2" casters available for added strength and mobility.

SIDE LINKS

Conveyor side links are made of 7 gauge steel and feature bolted construction.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

BOX STOP/HANDLE

Standard retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

Two year factory warranty.

Flexible Material Handling

SMART SOLUTIONS™

www.flexmh.com
800-669-1501